



G50H-19-RASTM

For producing ASTM Rubber
Test Slabs in accordance
with ASTM D3182

FEATURING Accu-Heat™
Heat Tube Platens
Accurate and Uniform to $\pm 1^\circ\text{F}$

specifications

- 8 - 50 ton compression force (adjustable)
- 19" L-R x 19" F-B fully guided heated steel Accu-Heat™ platens
- 500° F max operating temperature
- 8" - 16" open daylight
- 0" - 8" closed daylight
- 7" bore JIC style clamp cylinder
- 8" stroke
- 70 IPM closing speed
- 5 IPM pressing speed
- 70 IPM opening speed
- Weight: 3,950 lbs.
- Dimensions: 49" w x 49" d x 70" h

features

- Built-in lift truck tubes
- Allen Bradley MicroLogix 1200 programmable controller with PanelView 300 Micro operator interface
- Cycle counter through PLC
- Proximity switches to control "slow close" position and "cycle reset"
- Clamp pressure relief valve and gauge
- Automatic bump
- Multi channel digital chart recorder for pressure and temperature (optional)
- Air cooled heat exchanger (optional, not pictured)



CARVER

Wabash MPI

1569 Morris St., P.O. Box 298, Wabash, IN 46992-0298 USA

Phone: 260-563-1184 Fax: 260-563-1396

Email: wabashmpi@acscorporate.com, Internet: www.wabashmpi.com

All data subject to change without notice ©2019 Wabash MPI

ISO 9001:2015
Certified

